



## FLEX IPS 2221

---



## Classification Code

---

2221

## Applications

---

Suitable for installations where pipes are not subject to high compressions or impacts.

## Features

---

- Made of PVC
- Self-extinguishing
- Compression resistance: 320 N

## Advantages

---

- Available with and without wire-guide
- Packed with 100 % recyclable and UV resistant polyethylene film.

## Technical info


---

					
<b>PVC</b>	LEGGERO LIGHT LÉGER LIGERO LEICHT	LEGGERO LIGHT LÉGER LIGERO LEICHT			Autoestinguente Self-extinguishing Auto-extinguible No propagador de la llama Selbstverlöschend
	<b>2</b> 320N	<b>2</b> 1J	<b>2</b> -5°C	<b>1</b> +60°C	

### Colours

Grey

### Packaging info

						
IPS16 IPS20 IPS25 IPS32 IPS40 IPS50	IPS16F IPS20F IPS25F IPS32F - -	16 20 25 32 40 50	10,7 14,1 18,2 24,2 32,4 41,2		50 50 50 25 25 25	7.650 4.200 2.600 1.800 1.075 800

### Standards

- EN 61386.1
- EN 61386.22

### Trademarks



Sede Legale: via Garibaldi, 44  
Bergamo (Almenno San Salvatore) - 24031  
Cap. Soc. € 600.000 i.v. - C.C.I.AA. REA BG 97263  
Reg. Imp. BG 024-4701

Sede Commerciale e amministrativa: via XXV Aprile, 15  
Bergamo (Almenno San Bartolomeo) - 24030  
Tel. +39.035.554211 - Fax. +39.035.554200  
P.IVA 00216340166